# **CET246 Electronic Design Automation**

Connectors

David J. Broderick, Ph.D.

September 17, 2018

Central Connecticut State University

### Introduction



1


## **Electrical Requirements**

Questions to ask regarding each connector:

- 1. How many Signals?
- 2. High frequency?
- 3. Low-level analog?
- 4. High voltage?
- 5. High current?



# Size, Space, and Weight Requirements



# **Environmental Requirements**





High temperature



## **International Protection Marking**

### First Digit:

Solid particle protection

- 0. No protection
- 1. (>50 mm) Large Objects
- 2. (>12.5 mm) Finger width
- 3. (>2.5 mm) Small tools
- 4. (>1 mm) Wires, screws
- 5. Dust protected
- 6. Dust tight

### **Second Digit:**

Liquid ingress protection

- 0. No protection
- 1. Dripping Water, Upright
- 2. Dripping Water, 15° Tilt
- 3. Spraying Water, 60° Tilt
- 4. Splashing Water
- 5. Water Jets, 6.3 mm nozzle
- 6. Powerful water jets, 12.5 mm nozzle
- 7. Immersed, up to 1 meter
- 8. Immersed, over 1 meter

## **Industry Standards**


- OEM by agreement or Regulatory
- FDA medical
- SAE automotive
- MIL defense
- FAA- aerospace
- IEEE- interoperability





## Reliability


- Mating/Unmating Cycles
- Mean Time Before/To Failure (MTBF/MTTF)



### **Termination**

#### What does it connect to?

- PCB
- Wire
- Crimped
- Soldered
- Press fit



### Board Headers shrouded/unshrouded






#### Press fit



#### D Sub-miniature



#### RJ-XX




#### Screw terminals



## Barrel/Audio Jack



#### IC Sockets



#### British Naval Connector - BNC

